

FLOOD LIGHT





HD-S02L04WX | Narrow Beam Flood Light | 4*3W



Technical data

Wattage	12 WATT
Lumen	840 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø130*H178mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S02L09WX | Narrow Beam Flood Light | 9*3W



Technical data

Wattage	27 WATT
Lumen	840 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø182*204mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S02L16WX | Narrow Beam Flood Light | 16*3W



Technical data

Wattage	48 WATT
Lumen	3360 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø232*248mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S03N06WX | Outdoor Spot Light | 6*2W



Technical data

Wattage	12 WATT
Lumen	840 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø110*110*H150mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S01N04WX | Outdoor Spot Light | 9*2W



Technical data

Wattage	18 WATT
Lumen	1260 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø135*115*H180mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S03N18WX | Outdoor Spot Light | 18*2W



Technical data

Wattage	36 WATT
Lumen	2520 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø170*130*H230mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S03N54WX | Flood Light | 54*1.5W



Technical data

Wattage	81 WATT
Lumen	5670 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø235*290mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S03L20WX | Narrow Beam Flood Light | 20*2.5W



Technical data

Wattage	50 WATT
Lumen	1260 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø235*290mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S04N16WX | Outdoor Spot Light | 16W



Technical data

Wattage	16 WATT
Lumen	1120 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	L125*W125*H188mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S04N24WX | Flood Light | 24W



Technical data

Wattage	24 WATT
Lumen	1680 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	L150*W150*H218mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S04N36WX | Flood Light | 36W



Technical data

Wattage	36 WATT
Lumen	2520 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	L190*W190*H265mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S05C15WX | Outdoor Spot Light | 15W



Technical data

Wattage	15 WATT
Lumen	1050 lm
Input Voltage	220V / 24V
Beam Angle	12°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Φ100H170mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S05C25WX | Flood Light | 25W



Technical data

Wattage	25 WATT
Lumen	1750 lm
Input Voltage	220V / 24V
Beam Angle	18°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø130H220mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S05C50WX | Flood Light | 50W



Technical data

Wattage	50WATT
Lumen	3500 lm
Input Voltage	220V / 24V
Beam Angle	24°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø200H310mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S05C80WX | Outdoor Spot Light | 80W



Technical data

Wattage	80 WATT
Lumen	5600 lm
Input Voltage	220V / 24V
Beam Angle	24°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø230H345mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S06C05WX | Outdoor Spot Light | 5W



Technical data

Wattage	5 WATT
Lumen	350 lm
Input Voltage	220V / 24V
Beam Angle	24°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø80*135*185mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S06C10WX | Outdoor Spot Light | 10W



Technical data

Wattage	50WATT
Lumen	700 lm
Input Voltage	220V / 24V
Beam Angle	24°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø80*135*185mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S06C15WX | Outdoor Spot Light | 15W



Technical data

Wattage	15 WATT
Lumen	1050 lm
Input Voltage	220V / 24V
Beam Angle	24°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø80*135*185mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-HD-S07N03Wx | Floor Mount Spot Light | 6W



Technical data

Wattage	6 WATT
Lumen	420 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø110mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S07N06WX | Floor Mount Spot Light | 18W



Technical data

Wattage	18 WATT
Lumen	1260lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Ø130mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S06N09WX | Outdoor Spot Light | 18W



Technical data

Wattage	15 WATT
Lumen	1260 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	φ100*135*185mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S08N18WX | Flood Light | 18W



Technical data

Wattage	18 WATT
Lumen	1260 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	144*160*53MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S08N24WX | Flood Light | 24W



Technical data

Wattage	24 WATT
Lumen	1680lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	168*160*53MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S08N36WX | Outdoor Spot Light | 36W



Technical data

Wattage	3 WATT
Lumen	2520 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	302*160*53MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S09N72WX | Flood Light | 108W



Technical data

Wattage	108 WATT
Lumen	7560 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	200*93*367 MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S09N99WX | Flood Light | 200 W



Technical data

Wattage	200 WATT
Lumen	14000 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	200*93*505MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S09N72WX | Flood Light | 400 W



Technical data

Wattage	400 WATT
Lumen	28000 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	410*93*505 MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S08N54WX | Super Narrow Flood Light | 96W



Technical data

Wattage	96 WATT
Lumen	6720 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	200*93*367 MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S09N48WX | Super Narrow Flood Light | 144 W



Technical data

Wattage	144 WATT
Lumen	10800 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	200*93*505 MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S09296WX | Super Narrow Flood Light | 288W



Technical data

Wattage	288 WATT
Lumen	20160 lm
Input Voltage	220V / 24V
Beam Angle	3° to 8°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	410*93*505 MM
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S01N03WX | Outdoor Spot Light | 3W



Technical data

Wattage	3 WATT
Lumen	270 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	65*65*95mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S01N04WX | Outdoor Spot Light | 4*3W



Technical data

Wattage	4*3 WATT
Lumen	840 lm
Input Voltage	220V / 24V
Beam Angle	10° to 80°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	110*110*150mm
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included

HD-S01N06WX | Outdoor Spot Light | 6W



Technical data

Wattage	6 WATT
Lumen	420 lm
Input Voltage	220V / 24V
Beam Angle	30°
Color	RGB / RGBW/ Single Color
Control Type	DMX512 / Switch/ Dali
Size	Nil
IP Rating	IP65
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light Source	LED
Screws	Stainless steel
Gasket	Silicone rubber
Cover	Tempered glass
Cable Gland	Double nickel-plated brass cable gland PG11
Power Cable	1m power cable included